




- (51) International Patent Classification⁷:** H01J 35/10, 35/30
- (21) International Application Number:** PCT/IB2004/002324
- (22) International Filing Date:** 15 July 2004 (15.07.2004)
- (25) Filing Language:** English
- (26) Publication Language:** English
- (30) Priority Data:** 60/488,675 18 July 2003 (18.07.2003) US
- (71) Applicant (for all designated States except US):** KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor; and**
- (75) Inventor/Applicant (for US only):** HEUSCHER, Dominik, J. [US/US]; 595 Miner Road, Cleveland, OH 44143 (US).
- (74) Common Representative:** KONINKLIJKE PHILIPS ELECTRONICS N.V.; c/o LUNDIN, Thomas, M., 595 Miner Road, Cleveland, OH 44143 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GI, GR, GM, HN, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

- (54) Title: CYLINDRICAL X-RAY TUBE FOR COMPUTED TOMOGRAPHY IMAGING**



- (57) Abstract:** A computed tomography imaging system includes an x ray tube (12, 212) that injects an x ray conebeam into an examination region (14). The x ray tube (12, 212) includes a rotating cylindrical anode (30, 230, 330, 430) having a target outer surface region. The cylindrical anode (30, 230, 330, 430) rotates about a longitudinally aligned cylinder axis (32). Electrons are accelerated toward a selected spot on the target outer surface region of the cylindrical anode (30, 230, 330, 430). Electrostatic or electromagnetic deflectors (64, 68) sweep the selected spot back and forth across the target outer surface region of the cylindrical anode (30, 330, 430). The imaging system further includes a rotating gantry (22) that revolves the x ray tube (12, 212) about the examination region (14) around a rotation axis that is parallel to the cylindrical axis, and an x-ray detector (16) arranged to detect x rays after said x rays pass through the examination region (14).

11 August 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.